

FRESNELS LED



2700K°



6500K°

SPL-200/BI/MO SPL-200/BI/PO

FRESNEL LED STUDIO 200W VARIABLE WHITE 2700K° TO 6500K°

- High efficient led 200w Bi-colour CRI ≥ 95
- Power consumption: 200w
- Adjustable colour temperature: 2700K° to 6500K°
- Flicker free
- Power requirements 90V-240V 50/60Hz
- Control method: DMX or local (manual) dimming
- Powercom for power daisy chain
- Fresnel lens Ø 150mm
- MO manual operation version - PO pole operation version

ACCESSORIES




Barndoor 8-leaf



Colour conversion & Diffusion filter frame

DIMENSIONS




L 380mm (14.96")
W 306mm (12.04")
H 542mm (21.33")
9,500 kg

PHOTOMETRIC DATA

Spot					
Distance	4 mts	5 mts	6 mts	7 mts	8 mts
Center beam	3810 lux	2430 lux	1680 lux	1203 lux	990 lux
Light beam Ø	1,10 mts	1,60 mts	1,80 mts	2,00 mts	2,30 mts
CCT K°	6300	6300	6300	6300	6300
CRI	95	95	95	95	95

Center beam	2975 lux	1900 lux	1340 lux	952 lux	750 lux
CCT K°	2825	2825	2825	2825	2825
CRI	96,5	96,5	96,5	96,5	96,5



Flood					
Distance	4 mts	5 mts	6 mts	7 mts	8 mts
Center beam	1400 lux	900 lux	630 lux	480 lux	380lux
Light beam Ø	2,40 mts	3,00 mts	3,50 mts	4,20 mts	4,40 mts
CCT K°	6580	6580	6580	6580	6580
CRI	95	95	95	95	95

Center beam	1106 lux	703 lux	495 lux	365 lux	295 lux
CCT K°	2890	2890	2890	2890	2890
CRI	96,7	96,5	96,7	96,7	96,7

KIT CONTENTS

- Lamphead
- Barndoor 8-leaf
- Filter frame
- Safety grid
- 2 m power supply cable