

FRESNELS LED



6500K°




2700K°

53-20/BI

FRESNEL LED COMPACT 120W VARIABLE WHITE 2700K° TO 6500K°

- High efficient led 120w Bi-colour CRI ≥ 95
- Power consumption: 120w
- Power requirements: 90V-240V 50/60Hz
- Control method: DMX or local (manual) dimming
- Adjustable Colour temperature: 2700K° to 6500K°
- Flicker free
- Fresnel lens Ø 120mm
- Powercom for power daisy chain
- MO manual operation version - PO pole operation version

ACCESSORIES




Barndoor 8-leaf



Colour conversion & Diffusion filter frame


DIMENSIONS



L 300mm (11,81")
W 200mm (7,87")
H 400mm (15,75")
4,900 kg

PHOTOMETRIC DATA

Spot			
Distance	2 mts	3 mts	4 mts
Center beam	2680 lux	1375 lux	785 lux
Light beam Ø	1,00 mts	1,60 mts	2,00 mts
CCT K°	6500	6500	6500
CRI	95	95	95



Flood			
Distance	2 mts	3 mts	4 mts
Center beam	483 lux	270 lux	172 lux
Light beam Ø	2,80 mts	4,30 mts	5,50 mts
CCT K°	6300	6300	6300
CRI	95	95	95

KIT CONTENTS

- Lamphead
- Barndoor 8-leaf
- Filter frame
- Safety grid
- 2 m power supply cable