

FRESNELS LED



53-20/MO 53-20/PO

FRESNEL LED COMPACT 120W

- High efficient led 120w CRI ≥ 95
- Power consumption: 120w
- Power requirements: 90V-240V 50/60Hz
- Control method: DMX or local (manual) dimming 0 to 100%
- Colour temperature: 5600K° or 3200K°
- Flicker free
- Fresnel lens Ø 120mm
- Powercom for power daisy chain
- MO manual operation version - PO pole operation version

ACCESSORIES




Barndoor 4-leaf



Colour conversion & Diffusion filter frame

DIMENSIONS




L 300mm (11,81")
 W 200mm (7,87")
 H 400mm (15,75")
 5 kg

PHOTOMETRIC DATA

Spot

Distance	4 mts	5 mts	6 mts	7 mts	8 mts
Center beam	4300 lux	2650 lux	1870 lux	1390 lux	1049 lux
Light beam Ø	1,00 mts	1,50 mts	2,00 mts	2,50 mts	3,00 mts
CCT K°	5580	5580	5580	5580	5580
CRI	95	95	95	95	95

Center beam	5230 lux	3245 lux	2190 lux	1560 lux	1200 lux
Light beam Ø	1,00 mts	1,50 mts	2,00 mts	2,50 mts	3,00 mts
CCT K°	3100	3100	3100	3100	3100
CRI	95	95	95	95	95



Flood

Distance	4 mts	5 mts	6 mts	7 mts	8 mts
Center beam	1710 lux	1080 lux	780 lux	580 lux	440 lux
Light beam Ø	2,20 mts	3,40 mts	4,30 mts	5,60 mts	6,50 mts
CCT K°	5800	5800	5800	5800	5800
CRI	95	95	95	95	95

Center beam	2000 lux	1280 lux	880 lux	650 lux	495 lux
Light beam Ø	2,20 mts	3,40 mts	4,30 mts	5,60 mts	6,50 mts
CCT K°	3198	3198	3198	3198	3198
CRI	95	95	95	95	95

KIT CONTENTS

Lamphead
 Barndoor 4-leaf
 Colour frame
 Safety grid
 2 m power supply cable