

FRESNELS LED





SPL-500/XL/BI/MO SPL-500/XL/BI/PO


FRESNEL LED STUDIO 500W VARIABLE WHITE 2700K° TO 6500K°

- High efficient led 500w Bi-colour CRI ≥ 95
- Power consumption: 500w
- Adjustable colour temperature: 2700K° to 6500K°
- Dimming 0 to 100%
- Flicker free
- Power requirements 90V-240V 50/60Hz
- Control method: DMX or local (manual) dimming
- Powercom for power daisy chain
- Fresnel lens Ø 250mm
- MO manual operation version - PO pole operation version

ACCESSORIES

-  Barndoor 8-leaf
-  Colour conversion & Diffusion filter frame

DIMENSIONS




L 405mm (15.94")
W 480mm (18.89")
H 630mm (24.80")
 16,100 kg

PHOTOMETRIC DATA

Spot						
Distance	4 mts	5 mts	6 mts	7 mts	8 mts	9 mts
Center beam	12180 lux	8145 lux	5747 lux	4195 lux	3357 lux	2693 lux
Light beam Ø	3,00 mts	3,30 mts	3,50 mts	4,00 mts	4,60 mts	5,10 mts
CCT K°	6500	6500	6500	6500	6500	6500
CRI	96	96	96	96	96	96

Center beam	8158 lux	5240 lux	3686 lux	2928 lux	2121 lux	1697 lux
CCT K°	2800	2800	2800	2800	2800	2800
CRI	97	97	97	97	97	97



Flood						
Distance	4 mts	5 mts	6 mts	7 mts	8 mts	9 mts
Center beam	1342	833 lux	595 lux	440 lux	361 lux	295 lux
Light beam Ø	6,00 mts	7,00 mts	8,00 mts	9,00 mts	10,00 mts	11,00 mts
CCT K°	6510	6510	6510	6510	6510	6510
CRI	96	96	96	96	96	96

Center beam	868 lux	565 lux	408 lux	295 lux	235 lux	196 lux
CCT K°	2780	2780	2780	2780	2780	2780
CRI	97	97	97	97	97	97

KIT CONTENTS

- Lamphead
- Barndoor 8-leaf
- Filter frame
- Safety grid
- 2 m power supply cable