



MODELOS

SPL-100/BAT Battery Power Operation V-Mount 14,8V

- High efficient led 100W.
- Power consumption: 100W.
- Power requirements: Battery Operation 14,8V or 90V-240V 50/60Hz.
- Control method: DMX or Local (manual) dimming.
- Colour temperature: 3200K° or 5600K°.
- Flicker Free.
- Fresnel lens Ø 6" (150mm)
- Powercom for power daisy chain.
- Warranty 2 years

FRESNEL LED LOCATION 100W PARA BATERIA

FRESNELS LED

Fresnels LED 100W built with aluminum profiles and steel, on modern and compact design, ensuring maximum dissipation and lightweight. Leds available for 3200K° or 5600K°, offering high colour rendering (CRI average >95),

Efficient optical system uses high quality reflector and fresnel lens glass to ensure maximum lighting performance. Saves up to 85% in energy consumption compared to halogen fresnels and a considerable reduction of heat emission.

The FRESNEL LED can be controlled via DMX from the console or manually by a potentiometer located on the control panel of the same fresnel Led. The control panel has an LCD and buttons to set the display DMX address, also select the type of DMX-Manual control, allowing display the percentage of light output and the LED voltage, as well as the temperature inside the equipment and its system electronic, and other parameters.


They are equipped with high quality drivers.

Flicker free, and noiseless turbine, to ensure maximum extension of the lifetime of the LED. Supplied with PowerCom connectors

FRESNEL SPL-100 5700K°

SPOT					
Distancia	4 mts	5 mts	6 mts	7 mts	8 mts
Center beam	4300 lux	2950 lux	1870 lux	1390 lux	1049 lux
Light beam diameter	1,50 mts	1,80 mts	2,00 mts	2,10 mts	2,20 mts
CCT	5580	5580	5580	5580	5580
CRI	91,5	91,5	91,5	91,5	91,5

Center beam	5200 lux	3245 lux	2190 lux	1560 lux	1200 lux
Light beam diameter	1,50 mts	1,80 mts	2,00 mts	2,10 mts	2,20 mts
CCT	3100	3100	3100	3100	3100
CRI	92	92	92	92	92



FLOOD					
Distancia	4 mts	5 mts	6 mts	7 mts	8 mts
Center beam	1710 lux	1080 lux	780 lux	580 lux	440 lux
Light beam diameter	2,80 mts	3,10 mts	3,90 mts	4,50 mts	5,00 mts
CCT	5780	5780	5780	5780	5780
CRI	91,5	91,5	91,5	91,5	91,5


Center beam	2000 lux	1280 lux	880 lux	650 lux	495 lux
Light beam diameter	2,80 mts	3,10 mts	3,90 mts	4,50	5,00
CCT	3188	3188	3188	3188	3188
CRI	92	92	92	92	92



L 332mm (13.07")

W 333mm (13.11")

H 566mm (22.28")



FORNECIDO COM:

- V-Mount Battery Holder
- Barndoor 4-leaf.
- Filter frame.
- Safety grid.
- 2 m power supply cable

